

## **APPLICATIONS**

Ideal for residential security lighting, building perimeters, and building entrances.

Mounting Plate

Cast aluminum.

Finish White or Black

Mounting

Fits over a standard octagon box.

**SPECIFICATIONS** 

#### Construction

The MS-LED-1H-180 has a 180 degree sensor and comes with one LED flood and mounting plate.

#### Photo Electric Control


Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications.

### LED Flood

Extruded aluminum with clear lens. Unit has nine LEDs providing 1800 lumens out of the fixture.

## DIMENSIONS

6.3" (16.1cm) 8.3" (21.0cm)



The MS-LED-1H-180 is equivalent to a 300 watt quartz unit with a total of 1800 lumens out of the fixture. Whenever the motion sensor detects motion the floodlight automatically turn on. The sensor is adjustable and can turn the light on from 5 seconds to 12 minutes.

Project	
Туре	
Date	
Notes	

Equivalent to	150 PAR Inc
Watts	27W
Lumens	1,800
Efficiency	66.7 lumens/watt

LED Life	100,000 hours
Colour Temperature	4,000K
Warranty	5 Years
Operating Temperature	-30°C to +50°C
Certification	cCSAus



**MS-LED-1H** Sensor Activated Light

RAB DESIGN LIGHTING INC.



# DETECTION RANGE

